

Monad Electronics

G1-805, Sitapura Industrial Area,

Tonk Road, Jaipur-302022

Phone:- +91-141-277 1119, Fax:-+91-141-2550005

Website:- www.monadindia.com

Email:- mail@monadindia.com, monadindia@yahoo.com



Monad Electronics, India

Introduction

Winner of National Award for year 2009-2010 in R&D

Monad Electronics is An ISO 9001:2000 certified company, which has over the last 13 years been involved in the business of Exporting, designing & manufacturing, Electronics Industrial products, Testing equipments , sensors and related indicating and controlling devices and allied products related to Data logging & Acquisition.

We are specialized in providing consultancy for itemized engineering Test ring and Projects. We are also interested in taking - up the project development, recommending and mfg. sensing and related components, service providing in installation & commissioning.

We are in this field from last 13 years and also Exporting our products to USA, Germany, Belgium, Turkey, Australia, UAE and African countries. We have good track record of import substitute high end equipment development and supplying to leading industries and government institutes.



Digital Wireless Dynamometer

MNT-W5

Monad MNT-W5 is a rugged portable dynamometer for measuring tension, traction and weight in capacities from 100 Kgf to 500 T.

Easy to read 6 Digit LCD display with inbuilt Battery backup.

Unique design providing maximum readability. Accuracy, safe, portable and ruggedly dependable System.

It comes with Wireless hand held Remote terminal with both Display & Keyboard.

Advance features are available like,

- * RS232 out put
- * In built Datalogging



Monad Electronics, India



Technical System

MNT-W5

Enclosure: Designed to IP55, Suitable for continuous outdoor use.

Accuracy: 0.2%

Repeatability: 0.1%

Ultimate overload: 200%.

Safe overload: 150% of capacity

Body protection: Alloy steel, electroless-nickel plated.

Shackles: Forged industry standard anchor shackles(Optional).

Display: 16X2 Alphanumeric LCD

Display update rate: 2 times per second.

Calibration: Software Calibration.

Battery life: 6-10 hours typical use with > 80 % Charge condition

Operating temperature: 0 to 60° C

